

LED Floodlights (SMD)

Key Features

- ✓ High Output (>160lm/W) CREE SMD
- ✓ AC85 - 265V
- ✓ 50,000 Hours Lifespan
- ✓ SABS Tested
- ✓ SANS/IEC 60598-1 & 60598-2-5 Compliant



1000W



50W



100W



150W



200W



300W




400W



500W



600W



800W

Product Code	Description	Power (Watt)	Lumen Output	Efficiency (lm/W)	CCT / Colors Available	Order Code	SABS Tested
MEFLM-50W	50W SMD Modular Floodlight	50	8000	160	3000K, 4000K, 5000K, 6000K	HMFL50<COLOR>CRST	Y
MEFLM-100W	100W SMD Modular Floodlight	100	16000	160	3000K, 4000K, 5000K, 6000K	HMFL100<COLOR>CRST	Y
MEFL-150W	150W SMD Modular Floodlight	150	24000	160	3000K, 4000K, 5000K, 6000K	HMFL150<COLOR>CRST	Y
MEFL-200W	200W SMD Modular Floodlight	200	32000	160	3000K, 4000K, 5000K, 6000K	HMFL200<COLOR>CRST	Y
MEFL-300W	300W SMD Modular Floodlight	300	48000	160	3000K, 4000K, 5000K, 6000K	HMFL300<COLOR>PHST	Y
MEFL-400W	400W SMD Modular Floodlight	400	64000	160	3000K, 4000K, 5000K, 6000K	HMFL400<COLOR>CRST	Y
MEFL-500W	500W SMD Modular Floodlight	500	80000	160	3000K, 4000K, 5000K, 6000K	HMFL500<COLOR>CRST	Y
MEFL-600W	600W SMD Modular Floodlight	600	96000	160	3000K, 4000K, 5000K, 6000K	HMFL600<COLOR>PHST	Y
MEFL-800W	800W SMD Modular Floodlight	800	128000	160	3000K, 4000K, 5000K, 6000K	HMFL800<COLOR>PHST	Y
MEFL-1000W	1000W SMD Modular Floodlight	1000	160000	160	3000K, 4000K, 5000K, 6000K	HMFL1000<COLOR>PHST	Y

Order Information

HMFL	400	6000	CR
Type	Watt	Color	Range

Colors: 3000, 4000, 6000.
e.g. 500W SMD Modular Floodlight -
HMFL500**6000**CR

